ARCHITECTURAL OUTDOOR EMERGENCY

The ELLIPTICA (EL) Series Emergency Light provides an attractive solution to applications that require low profile egress emergency lighting with rugged durability and good looks. Constructed of die-cast aluminum with a polycarbonate refractor and finished epoxy powder coat, the ELLIPTICA is gasket sealed and ready for use in both indoor and outdoor applications.


FEATURES


- Wet location listed for indoor or outdoor applications 32° 122° F
- Optional Cold temperature package for -4° 122° F applications
- · Rugged die-cast aluminum construction
- Durable powder coat finish available in Bronze, White, Black and Brushed Aluminum
- Snap fit assembly with vandal resistant latch clips; no visible hardware
- · Gasket sealed to suit universal junction boxes
- · Conduit entry provided on top of unit
- Available as a 6 volt DC remote fixture
- UV stabilized polycarbonate refractor resists yellowing and provides uniform distribution
- · Two 6 watt high output Xenon lamps for superior illumination
- · Optional decorative colored night light
- · Integral push-to-test switch

ELECTRONICS

- Self Test / Self Diagnostic circuit is provided as standard thereby reducing manual testing obligations
- Easily visible Bi-Color LED diagnostic indicator
- Automated, 28 day, self test checks lamp, battery and electronic circuitry over a short one minute test. Extended 30 minute emergency duration tests are automatically conducted every six months
- Premium long life high temperature rated Nickel Cadmium battery
- Sealed externally accessible test switch for manual momentary test operation
- Field selectable 120 or 277 VAC input
- Brownout sensing assures emergency illumination during periods of low line voltage
- Self-compensating solid state Constant Current Charger provides extended float life and rapid recharge
- Zero current LVCO ensures positive charge acceptance following an extended discharge
- Listed UL 924 Damp and Wet locations







SIGN SERIES	HOUSING	NIGHT LIGHT	OPTIONS
EL6 SELF-POWERED ELR 6 VOLT DC 12 WATT REMOTE (2-6 watt lamps)	B BLACK W WHITE BRZ BRONZE BAL BRUSHED ALUMINUM	NLW WHITE LED NLG GREEN LED NLA AMBER LED NLB BLUE LED	CT COLD TEMP OPERATION (-4° F)

WARRANTY

The Elliptica comes from the factory with a three year limited warranty.

AGENCY APPROVAL

ETL listed, per UL Standard 924 and Life Safety Code NFPA 101 (1991). Meets requirements of National Electrical Code Article 500, Class I and II conditions.



